



QUICK FIX® 3+ 36V Power Supply

Predecessor: 014-031 002-012 EUV-150S036SV

Description

The days when you needed a separate socket for each element of The days when you needed a separate socket for each element of your lighting installation are now finally consigned to history with our design protected QuickFix™ system: Using this connector system, multiple branded 230-volt products may be connected together with no problem – and this is also true for 36-volt products. Each QuickFix™ product is individually quality tested to meet the IP67 rating - seeping moisture presents no danger to its continued operation. The QuickFix™ cable is available in the colors white and black; cables for low-voltage products can be ordered in the colors transparent and green ordered in the colors transparent and green

Assembly:

230V LED products should always be installed under power as this is the only way to check the polarity. All new products have modified plugs ensuring the correct polarity.

Product data



Size (L-W-H): 19.9 x 6.75 x 3.95 cm

Max. Wattage: 120 W

Mains voltage: 100-240 V AC 50-60Hz Operating voltage: 36 V DC

Operating mode: Outlets: 1 Connectable: no













Packaging - Product

Type of Packaging: Sales Box EAN-Code: 9120049839438 Size (L-W-H): 32.8 x 13 x 4.9 cm Weight: 1 kg Produkts/Packaging: 1

Packaging - Inner Box

Type of Packaging: White carton EAN-Code: 9120049839452 Size (L-W-H): 33.7 x 25.9 x 14.3 cm Weight: 5 kg Produkts/VPE: 5

Packaging - Shipping

Type of Packaging: Brown carton EAN-Code: 9120049839445 Size (L-W-H): 54 x 35.5 x 31 cm Produkts/VPE: 20