



Predecessor: 015-013 002-110

Description

The days when you needed a separate socket for each element of The days when you needed a separate socket for each element of your lighting installation are now finally consigned to history with our design protected QuickFix™ system: Using this connector system, multiple branded 230-volt products may be connected together with no problem – and this is also true for 36-volt products. Each QuickFix™ product is individually quality tested to meet the IP67 rating - seeping moisture presents no danger to its continued operation. The QuickFix™ cable is available in the colors white and black; cables for low-voltage products can be ordered in the colors transparent and green ordered in the colors transparent and green

Assembly:

230V LED products should always be installed under power as this is the only way to check the polarity. All new products have $\,$ modified plugs ensuring the correct polarity.

Product data



transparent

Length: 5.00 m Max. Wattage: 200 W Mains voltage: 36 V DC Operating voltage: 36 V DC
Operating mode: Power supply Outlets: 4 Connectable: yes





Packaging - Product

Type of Packaging: Blister EAN-Code: 9120079031390 Size (L-W-H): 22 x 30 x 0 cm Weight: 0.57 kg Produkts/Packaging: 1

Packaging - Inner Box

Type of Packaging: White carton EAN-Code: 9120079039501 Produkts/VPE: 4

Packaging - Shipping

Type of Packaging: Brown carton EAN-Code: 9120079036074