



Predecessor: 014-136 003-103

Description

The days when you needed a separate socket for each element of your lighting installation are now finally consigned to history with our design protected QuickFix™ system: Using this connector system, multiple branded 230-volt products may be connected together with no problem – and this is also true for 36-volt products. Each QuickFix™ product is individually quality tested to meet the IP67 rating - seeping moisture presents no danger to its continued operation. The QuickFix™ cable is available in the colors white and black; cables for low-voltage products can be ordered in the colors transparent and green.

Assembly:

230V LED products should always be installed under power as this is the only way to check the polarity. All new products have modified plugs ensuring the correct polarity.

Product data



Length: 100 cm Number of segments: 1 Max. Wattage: 1800 W Mains voltage: 220-240 V AC 50-60Hz Operating voltage: 220-240 V AC 50-60Hz Operating mode: Power supply Outlets: 1 Connectable: yes



С€□ IP67 😿 ЦК

Packaging - Product

Type of Packaging: Blister EAN-Code: 9120079033936 Size (L-W-H): 13 x 20 x 0 cm Weight: 0.14 kg Produkts/Packaging: 1

Packaging - Inner Box

Type of Packaging: White carton EAN-Code: 9120081796539 Size (L-W-H): 20 x 15 x 10 cm Weight: 0.83 kg Produkts/VPE: 5

Packaging - Shipping

Type of Packaging: Brown carton EAN-Code: 9120079038467 Size (L-W-H): 42 x 32 x 22 cm Weight: 7.17 kg Produkts/VPE: 40