



Successor: 001-034 014-920

Description

The days when you needed a separate socket for each element of your lighting installation are now finally consigned to history with our design protected QuickFix® system: Using this connector system, multiple branded 230-volt products may be connected together with no problem – and this is also true for 36-volt together with no problem – and this is also true for 35-voit products. Each Quick-Fix® product is individually quality tested to meet the IP44 rating - seeping moisture presents no danger to its continued operation. The Quick-Fix® cable is available in the colors white and black; cables for low-voltage products can be ordered in the colors transparent and green.

Assembly:

230V LED products should always be installed under power as this is the only way to check the polarity. All new products have modified plugs ensuring the correct polarity.

Product data



Size (L-W-H): 20 x 10 x 5 cm Max. Wattage: 3600 W
Mains voltage: 220-240 V AC 50-60Hz

Operating voltage: 220-240 V AC 50-60Hz Operating mode: Power supply

Outlets: 5 Connectable: no



Packaging - Product

Type of Packaging: White carton EAN-Code: 9120032336531 Size (L-W-H): 19 x 16 x 13 cm Weight: 0.6 kg Produkts/Packaging: 1

Packaging - Inner Box

Produkts/VPE: 5

Packaging - Shipping

Type of Packaging: Brown carton EAN-Code: 9120032336548 Size (L-W-H): 39 x 49 x 40 cm Weight: 29.8 kg Produkts/VPE: 20

