



# **QuickFix® Extension 1**

Successor: 002-104 015-012

#### **Description**

The days when you needed a separate socket for each element of The days when you needed a separate socket for each element of your lighting installation are now finally consigned to history with our design protected QuickFix™ system: Using this connector system, multiple branded 230-volt products may be connected together with no problem – and this is also true for 36-volt products. Each QuickFix™ product is individually quality tested to meet the IP67 rating - seeping moisture presents no danger to its continued operation. The QuickFix™ cable is available in the colors white and black; cables for low-voltage products can be ordered in the colors transparent and green ordered in the colors transparent and green

#### Assembly:

230V LED products should always be installed under power as this is the only way to check the polarity. All new products have modified plugs ensuring the correct polarity.

### **Product data**



transparent

Length: 100 cm Max. Wattage: 200 W Mains voltage: 36 V DC Operating voltage: 36 V DC Operating mode: Power supply Outlets: 1

Connectable: yes





### Packaging - Product

Type of Packaging: Blister EAN-Code: 9120032338535 Size (L-W-H): 13 x 20 x 0 cm Weight: 0.14 kg Produkts/Packaging: 1

# Packaging - Inner Box

Type of Packaging: White carton EAN-Code: 9120043102743 Size (L-W-H): 20 x 15 x 10 cm Weight: 0.83 kg Produkts/VPE: 5

## Packaging - Shipping

Type of Packaging: Brown carton EAN-Code: 9120032338702 Size (L-W-H): 42 x 32 x 22 cm Weight: 7.17 kg Produkts/VPE: 40