



## QuickFix® LED Main Connector

Predecessor: 014-419

**001-012**



### Description

The days when you needed a separate socket for each element of your lighting installation are now finally consigned to history with our design protected QuickFix™ system: Using this connector system, multiple branded 230-volt products may be connected together with no problem – and this is also true for 36-volt products. Each QuickFix™ product is individually quality tested to meet the IP67 rating - seeping moisture presents no danger to its continued operation. The QuickFix™ cable is available in the colors white and black; cables for low-voltage products can be ordered in the colors transparent and green.

#### Assembly:

230V LED products should always be installed under power as this is the only way to check the polarity. All new products have modified plugs ensuring the correct polarity.

### Product data

 white

Length: 1.50 m  
 Max. Wattage: 480 W  
 Mains voltage: 220-240 V AC 50-60Hz  
 Operating voltage: 220-240 V AC 50-60Hz  
 Operating mode: Power supply  
 Outlets: 1  
 Connectable: yes



QuickFix™ connection system

### Packaging - Product

Type of Packaging: Blister  
 EAN-Code: 9120079030522  
 Size (L-W-H): 17 x 25 x 0 cm  
 Weight: 0.255 kg  
 Produkts/Packaging: 1

### Packaging - Inner Box

Type of Packaging: White carton  
 EAN-Code: 9120079039419  
 Size (L-W-H): 28 x 20 x 8 cm  
 Weight: 1.425 kg  
 Produkts/VPE: 5

### Packaging - Shipping

Type of Packaging: Brown carton  
 EAN-Code: 9120079035220  
 Size (L-W-H): 42 x 30 x 26 cm  
 Weight: 9.13 kg  
 Produkts/VPE: 30