



QuickFix® RopeLight Adapter

Predecessor: 244-033

001-141



Description

Thanks to their double insulated rubber cable, our outdoor products are particularly robust and durable, thus offering a long service life. Each individual LED diode has a protective polycarbonate cap glued securely over it ensuring that no water or moisture can seep in - there is nothing to work loose and thereby interrupt the electrical current. The patented and quality-tested Quick-Fix® System meets IP rating IP44 and allows compatible 230V products to be extended and connected together without problems. Particularly suited for trees, facades and buildings.

Product data

 black

Length: 50 cm
 Max. Wattage: 740 W
 Mains voltage: 220-240 V AC 50-60Hz
 Operating voltage: 220-240 V AC 50-60Hz
 Operating mode:
 Outlets: 1
 Connectable: yes



QuickFix™ connection system

Packaging - Product

Type of Packaging: Blister
 EAN-Code: 9120079030294
 Size (L-W-H): 13 x 20 x 0 cm
 Weight: 0.122 kg
 Produkts/Packaging: 1

Packaging - Inner Box

Type of Packaging: White carton
 EAN-Code: 9120079039686
 Size (L-W-H): 28 x 18 x 8 cm
 Weight: 3.05 kg
 Produkts/VPE: 10

Packaging - Shipping

Type of Packaging: Brown carton
 EAN-Code: 9120079034964
 Size (L-W-H): 42 x 30 x 20 cm
 Weight: 6.9 kg
 Produkts/VPE: 50