



QuickFix® 36V RopeLight Adapter

Predecessor: 244-248

002-142



Description

The days when you needed a separate socket for each element of your lighting installation are now finally consigned to history with our design protected QuickFix™ system: Using this connector system, multiple branded 230-volt products may be connected together with no problem – and this is also true for 36-volt products. Each QuickFix™ product is individually quality tested to meet the IP67 rating - seeping moisture presents no danger to its continued operation. The QuickFix™ cable is available in the colors white and black; cables for low-voltage products can be ordered in the colors transparent and green.

Assembly:

230V LED products should always be installed under power as this is the only way to check the polarity. All new products have modified plugs ensuring the correct polarity.

Product data

 transparent

Length: 50 cm
 Max. Wattage: 740 W
 Mains voltage: 36 V DC
 Operating voltage: 36 V DC
 Operating mode:
 Outlets: 1
 Connectable: yes



QuickFix™ connection system

Packaging - Product

Type of Packaging: Blister
 EAN-Code: 9120079032847
 Size (L-W-H): 13 x 20 x 0 cm
 Weight: 0.122 kg
 Produkts/Packaging: 1

Packaging - Inner Box

Type of Packaging: White carton
 EAN-Code: 9120079039860
 Size (L-W-H): 28 x 18 x 8 cm
 Weight: 1.22 kg
 Produkts/VPE: 10

Packaging - Shipping

Type of Packaging: Brown carton
 EAN-Code: 9120079037514
 Size (L-W-H): 42 x 42 x 30 cm
 Weight: 6.9 kg
 Produkts/VPE: 50