

# **QuickFix® 3+ Main Connector**

Predecessor: 014-126 003-001

#### **Description**

The days when you needed a separate socket for each element of The days when you needed a separate socket for each element of your lighting installation are now finally consigned to history with our design protected QuickFix™ system: Using this connector system, multiple branded 230-volt products may be connected together with no problem – and this is also true for 36-volt products. Each QuickFix™ product is individually quality tested to meet the IP67 rating - seeping moisture presents no danger to its continued operation. The QuickFix™ cable is available in the colors white and black; cables for low-voltage products can be ordered in the colors transparent and green ordered in the colors transparent and green

#### Assembly:


230V LED products should always be installed under power as this is the only way to check the polarity. All new products have modified plugs ensuring the correct polarity.

### **Product data**



Length: 1.50 m Max. Wattage: 1800 W Outlets: 1 Connectable: yes





### **Packaging - Product**

Type of Packaging: Blister EAN-Code: 9120049839957 Size (L-W-H): 17 x 25 x 0 cm Weight: 0.235 kg Produkts/Packaging: 1

# Packaging - Inner Box

Type of Packaging: White carton EAN-Code: 9120079039396 Size (L-W-H): 28 x 20 x 8 cm Weight: 1.325 kg Produkts/VPE: 5

## Packaging - Shipping

Type of Packaging: Brown carton EAN-Code: 9120049839964 Size (L-W-H): 42 x 30 x 26 cm Weight: 8.53 kg Produkts/VPE: 30