



## QuickFix® T-Connector Indoor

Predecessor: 015-076

**007-166**



### Description

The days when you needed a separate socket for each element of your lighting installation are now finally consigned to history with our design protected QuickFix™ system: Using this connector system, multiple branded 230-volt products may be connected together with no problem – and this is also true for 36-volt products. Each QuickFix™ product is individually quality tested to meet the IP67 rating - seeping moisture presents no danger to its continued operation. The QuickFix™ cable is available in the colors white and black; cables for low-voltage products can be ordered in the colors transparent and green.

#### Assembly:

230V LED products should always be installed under power as this is the only way to check the polarity. All new products have modified plugs ensuring the correct polarity.

### Product data

 transparent

Size (L-W-H): 40 x 20 x 0 cm

Number of segments: 1

Max. Wattage: 1500 W

Mains voltage: 220-240 V AC 50-60Hz

Operating voltage: 220-240 V AC 50-60Hz

Operating mode:

Outlets: 2

Connectable: yes



QuickFix™ connection system

### Packaging - Product

Type of Packaging: Blister

EAN-Code: 9120079031819

Size (L-W-H): 17 x 25 x 0 cm

Weight: 0.175 kg

Produkte/Packaging: 1

### Packaging - Inner Box

Type of Packaging: White carton

EAN-Code: 9120079039587

Size (L-W-H): 28 x 20.5 x 10 cm

Weight: 1 kg

Produkte/VPE: 5

### Packaging - Shipping

Type of Packaging: Brown carton

EAN-Code: 9120079036470

Size (L-W-H): 42 x 33 x 31 cm

Weight: 6.75 kg

Produkte/VPE: 30