



QuickFix® 3+ Divider 2

Successor: 003-121
014-134



Description

The days when you needed a separate socket for each element of your lighting installation are now finally consigned to history with our design protected QuickFix™ system: Using this connector system, multiple branded 230-volt products may be connected together with no problem – and this is also true for 36-volt products. Each QuickFix™ product is individually quality tested to meet the IP67 rating - seeping moisture presents no danger to its continued operation. The QuickFix™ cable is available in the colors white and black; cables for low-voltage products can be ordered in the colors transparent and green.

Assembly:

230V LED products should always be installed under power as this is the only way to check the polarity. All new products have modified plugs ensuring the correct polarity.

Product data

 black

Number of segments: 1
Max. Wattage: 1800 W
Mains voltage: 220-240 V AC 50-60Hz
Operating voltage: 220-240 V AC 50-60Hz
Operating mode:
Outlets: 2
Connectable: yes



QuickFix™ connection system

Packaging - Product

Type of Packaging: Blister
EAN-Code: 9120049835591
Size (L-W-H): 17 x 25 x 0 cm
Weight: 0.175 kg
Produks/Packaging: 1

Packaging - Inner Box

Type of Packaging: White carton
EAN-Code: 9120049835614
Size (L-W-H): 28 x 20 x 8 cm
Weight: 1.025 kg
Produks/VPE: 5

Packaging - Shipping

Type of Packaging: Brown carton
EAN-Code: 9120049835607
Size (L-W-H): 42 x 30 x 26 cm
Weight: 6.73 kg
Produks/VPE: 30