



Successor: 003-161 014-150

#### **Description**

The days when you needed a separate socket for each element of The days when you needed a separate socket for each element of your lighting installation are now finally consigned to history with our design protected QuickFix™ system: Using this connector system, multiple branded 230-volt products may be connected together with no problem – and this is also true for 36-volt products. Each QuickFix™ product is individually quality tested to meet the IP67 rating - seeping moisture presents no danger to its continued operation. The QuickFix™ cable is available in the colors white and black; cables for low-voltage products can be ordered in the colors transparent and green ordered in the colors transparent and green

#### Assembly:

230V LED products should always be installed under power as this is the only way to check the polarity. All new products have  $\,$ modified plugs ensuring the correct polarity.

### **Product data**




Length: 50 cm Max. Wattage: 1800 W Mains voltage: 220-240 V AC 50-60Hz

Operating voltage: 220-240 V AC 50-60Hz

Operating mode: Connectable: yes





### Packaging - Product

Type of Packaging: Blister EAN-Code: 9120049835621 Size (L-W-H): 13 x 23 x 0 cm Weight: 0.19 kg Produkts/Packaging: 1

# Packaging - Inner Box

Type of Packaging: White carton EAN-Code: 9120049835645 Size (L-W-H): 20 x 20 x 8 cm Weight: 0.95 kg Produkts/VPE: 5

## Packaging - Shipping

Type of Packaging: Brown carton EAN-Code: 9120049835638 Produkts/VPE: 30