



## QuickFix® 36V Power Supply

Successor: 002-013  
014-151




### Description

The days when you needed a separate socket for each element of your lighting installation are now finally consigned to history with our design protected QuickFix® system: Using this connector system, multiple branded 230-volt products may be connected together with no problem - and this is also true for 36-volt products. Each Quick-Fix® product is individually quality tested to meet the IP44 rating - seeping moisture presents no danger to its continued operation. The Quick-Fix® cable is available in the colors white and black; cables for low-voltage products can be ordered in the colors transparent and green.

#### QuickFix™ Power Supply

The choice of the suitable transformer (power supply) principally depends on the size of the installation, which is defined by the number of LEDs (400 to 22,000 max. points of light) or the total output. Our transformers allow an output of 15 watts to 800 watts and comply with protection class IP44. The transformers cannot be connected with QuickFix™ 230 Volt LED products, as this is prevented, as an additional precaution, by the QuickFix™ plug-in system of the 36 V series.

### Product data

 transparent

Size (L-W-H): 24 x 7.2 x 4.2 cm  
Max. Wattage: 200 W  
Mains voltage: 100-240 V AC 50-60Hz  
Operating voltage: 36 V DC  
Operating mode:  
Connectable: no

### Packaging - Product

Type of Packaging:  
EAN-Code: 9120049835492  
Weight: 1.07 kg  
Produks/Packaging: 1

### Packaging - Inner Box

Type of Packaging: White carton  
EAN-Code: 9120049837762  
Produks/VPE: 5

### Packaging - Shipping

EAN-Code: 9120049835508  
Produks/VPE: 1



QuickFix™ connection system