

Successor: 001-127

014-307

#### **Description**

The days when you needed a separate socket for each element of your lighting installation are now finally consigned to history with our design protected QuickFix® system: Using this connector system, multiple branded 230-volt products may be connected together with no problem – and this is also true for 36-volt products. Each Quick-Fix® product is individually quality tested to meet the IP44 rating - seeping moisture presents no danger to its continued operation. The Quick-Fix® cable is available in the colors white and black; cables for low-voltage products can be ordered in the colors transparent and green

#### Assembly:

230V LED products should always be installed under power as this is the only way to check the polarity. All new products have modified plugs ensuring the correct polarity.

### **Product data**




Length: 62.5 cm Max. Wattage: 1800 W Mains voltage: 220-240 V AC 50-60Hz

Operating voltage: 220-240 V AC 50-60Hz Operating mode: Power supply

Outlets: 6

Connectable: yes





□ **( €** IP44 ▼

### Packaging - Product

Type of Packaging: Blister EAN-Code: 9120022119410 Size (L-W-H): 22 x 30 x 0 cm Weight: 0.57 kg Produkts/Packaging: 1

# Packaging - Inner Box

Type of Packaging: White carton EAN-Code: 9120043107601 Size (L-W-H): 40 x 30 x 10 cm Weight: 2.85 kg Produkts/VPE: 5

## Packaging - Shipping

Type of Packaging: Brown carton EAN-Code: 9120022119823 Size (L-W-H): 42 x 32 x 22 cm Weight: 6.28 kg Produkts/VPE: 10