



Sparestring

014-943




Description

The days when you needed a separate socket for each element of your lighting installation are now finally consigned to history with our design protected QuickFix® system: Using this connector system, multiple branded 230-volt products may be connected together with no problem – and this is also true for 36-volt products. Each Quick-Fix® product is individually quality tested to meet the IP44 rating - seeping moisture presents no danger to its continued operation. The Quick-Fix® cable is available in the colors white and black; cables for low-voltage products can be ordered in the colors transparent and green.

Assembly:

230V LED products should always be installed under power as this is the only way to check the polarity. All new products have modified plugs ensuring the correct polarity.

Product data

 LED warm white (30 LED)

 transparent

Length: 3.00 m
 Number of segments: 1
 Lamps per segment: 30
 Length per segment: 3.00 m
 Watt/segment: 2.05 W
 Watt: 2.05 W
 Mains voltage: 220-240 V AC 50-60Hz
 Operating voltage: 220-240 V AC 50-60Hz
 Operating mode:
 Connectable: yes



Packaging - Product

Type of Packaging: Blister
 EAN-Code: 9120032336050
 Size (L-W-H): 13 x 20 x 0 cm
 Weight: 0.21 kg
 Produkts/Packaging: 1

Packaging - Inner Box

Type of Packaging: White carton
 EAN-Code: 9120043103146
 Size (L-W-H): 38 x 28 x 9 cm
 Weight: 4.2 kg
 Produkts/VPE: 10

Packaging - Shipping

Type of Packaging: Brown carton
 EAN-Code: 9120032336067
 Size (L-W-H): 40 x 30 x 20 cm
 Weight: 9.1 kg
 Produkts/VPE: 40