

## QuickFix® Divider 2

Successor: 002-122  
015-010


### Description

The days when you needed a separate socket for each element of your lighting installation are now finally consigned to history with our design protected QuickFix™ system: Using this connector system, multiple branded 230-volt products may be connected together with no problem – and this is also true for 36-volt products. Each QuickFix™ product is individually quality tested to meet the IP67 rating - seeping moisture presents no danger to its continued operation. The QuickFix™ cable is available in the colors white and black; cables for low-voltage products can be ordered in the colors transparent and green.

#### Assembly:

230V LED products should always be installed under power as this is the only way to check the polarity. All new products have modified plugs ensuring the correct polarity.

### Product data

 transparent

Number of segments: 1  
Max. Wattage: 200 W  
Mains voltage: 36 V DC  
Operating voltage: 36 V DC  
Operating mode:  
Outlets: 2  
Connectable: yes



QuickFix™ connection system



### Packaging - Product

Type of Packaging: Blister  
EAN-Code: 9120032338511  
Size (L-W-H): 17 x 25 x 0 cm  
Weight: 0.175 kg  
Produkte/Packaging: 1

### Packaging - Inner Box

Type of Packaging: White carton  
EAN-Code: 9120043102705  
Size (L-W-H): 28 x 20 x 8 cm  
Weight: 1.025 kg  
Produkte/VPE: 5

### Packaging - Shipping

Type of Packaging: Brown carton  
EAN-Code: 9120032338702  
Size (L-W-H): 42 x 30 x 26 cm  
Weight: 6.73 kg  
Produkte/VPE: 30