



Successor: 002-130 015-014

#### **Description**

The days when you needed a separate socket for each element of The days when you needed a separate socket for each element of your lighting installation are now finally consigned to history with our design protected QuickFix™ system: Using this connector system, multiple branded 230-volt products may be connected together with no problem – and this is also true for 36-volt products. Each QuickFix™ product is individually quality tested to meet the IP67 rating - seeping moisture presents no danger to its continued operation. The QuickFix™ cable is available in the colors white and black; cables for low-voltage products can be ordered in the colors transparent and green ordered in the colors transparent and green

#### Assembly:

230V LED products should always be installed under power as this is the only way to check the polarity. All new products have modified plugs ensuring the correct polarity.

### **Product data**



transparent

Length: 1.30 m Number of segments: 1 Length per segment: 1.25 m Max. Wattage: 200 W Mains voltage: 36 V DC Operating voltage: 36 V DC Operating mode:

Outlets: 11 Connectable: yes





♠ C € IP44 ▼



Type of Packaging: Blister EAN-Code: 9120032338559 Size (L-W-H): 33 x 36 x 0 cm Weight: 1 kg Produkts/Packaging: 1

# Packaging - Inner Box

Type of Packaging: White carton EAN-Code: 9120043102781 Size (L-W-H): 40 x 30 x 10 cm Weight: 4 kg Produkts/VPE: 4

## Packaging - Shipping

Type of Packaging: Brown carton EAN-Code: 9120032338276 Size (L-W-H): 42 x 32 x 22 cm Weight: 8.58 kg Produkts/VPE: 8