



## QuickFix® Divider 3

Successor: 007-126  
015-074



### Description

The days when you needed a separate socket for each element of your lighting installation are now finally consigned to history with our design protected QuickFix® system: Using this connector system, multiple branded 230-volt products may be connected together with no problem – and this is also true for 36-volt products. Each Quick-Fix® product is individually quality tested to meet the IP44 rating - seeping moisture presents no danger to its continued operation. The Quick-Fix® cable is available in the colors white and black; cables for low-voltage products can be ordered in the colors transparent and green.

#### Assembly:

230V LED products should always be installed under power as this is the only way to check the polarity. All new products have modified plugs ensuring the correct polarity.

### Product data

 transparent

Length: 1.25 m  
Number of segments: 1  
Length per segment: 1.25 m  
Max. Wattage: 1500 W  
Mains voltage: 220-240 V AC 50-60Hz  
Operating voltage: 220-240 V AC 50-60Hz  
Operating mode:  
Outlets: 12  
Connectable: yes



QuickFix™ connection system

### Packaging - Product

Type of Packaging: Blister  
EAN-Code: 9120043102637  
Size (L-W-H): 33 x 36 x 0 cm  
Weight: 1 kg  
Produkte/Packaging: 1

### Packaging - Inner Box

Type of Packaging: White carton  
EAN-Code: 9120043102804  
Size (L-W-H): 40 x 30 x 10 cm  
Weight: 4 kg  
Produkte/VPE: 4

### Packaging - Shipping

Type of Packaging: Brown carton  
EAN-Code: 9120043102644  
Size (L-W-H): 42 x 32 x 22 cm  
Weight: 8.58 kg  
Produkte/VPE: 8