

# Sparestring

015-318




## Description

The days when you needed a separate socket for each element of your lighting installation are now finally consigned to history with our design protected QuickFix™ system: Using this connector system, multiple branded 230-volt products may be connected together with no problem – and this is also true for 36-volt products. Each QuickFix™ product is individually quality tested to meet the IP67 rating - seeping moisture presents no danger to its continued operation. The QuickFix™ cable is available in the colors white and black; cables for low-voltage products can be ordered in the colors transparent and green.

### Assembly:

230V LED products should always be installed under power as this is the only way to check the polarity. All new products have modified plugs ensuring the correct polarity.

## Product data

-  LED warm white ( 13 LED )
-  LED white ( 2 LED )
-  transparent

Length: 1.50 m  
 Number of segments: 1  
 Lamps per segment: 15  
 Flash-LED per segment: 2  
 Length per segment: 1.50 m  
 Watt/segment: 1.95 W  
 Watt: 1.95 W  
 Mains voltage: 220-240 V AC 50-60Hz  
 Operating voltage: 220-240 V AC 50-60Hz  
 Operating mode:  
 Connectable: yes

## Packaging - Product

Type of Packaging: Blister  
 EAN-Code: 9120049831685  
 Size (L-W-H): 13 x 20 x 0 cm  
 Weight: 0.12 kg  
 Produkts/Packaging: 1

## Packaging - Inner Box

Type of Packaging: White carton  
 EAN-Code: 9120049831708  
 Size (L-W-H): 38 x 28 x 9 cm  
 Weight: 3.6 kg  
 Produkts/VPE: 30

## Packaging - Shipping

Type of Packaging: Brown carton  
 EAN-Code: 9120049831692  
 Size (L-W-H): 40 x 30 x 20 cm  
 Weight: 7.9 kg  
 Produkts/VPE: 60